

TAG Inflatable Shelter

The Number One Shelter for Emergency Situations, Rapid Deployment

The Losberger TAG Inflatable Shelters can be deployed in less than 6 minutes with 2-3 people. Compact, lightweight and modular, TAG's are the perfect solution for first responders or disaster victims when reliability and speed are crucial.



Description

The Losberger Heavy-Duty TAG Inflatable Shelters are compact, lightweight, and modular. They can be deployed in less than six (6) minutes with two to three (2 to 3) people. Their speed and ease of deployment make them the ideal solution for emergency care, command posts, or all-purpose emergency shelters. The resistance and robust construction of TAG Inflatable Shelters, along with a set of accessories ensure an effective use on any kind of land.

The Losberger Heavy-Duty TAG Inflatable Shelters are modular in design. The shelters can be connected to each other in four (4) directions. They are made of durable, fire and UV-resistant, PVC-coated fabric (military grade 22 oz/sq yd), using High Frequency Welding (HFW) to construct the cover and floor into one enclosure. Available in four (4) sizes and four(4) colors.



List of Equipment

- Automatic pressure control system
- Internal partition walls
- Internal liners
- External sunshade
- Electric inflator
- Protective groundsheet
- Lighting
- Electrical distribution box
- Heating/AC systems
- Flooring
- Side door(s)
- Connecting & entrance modules
- Printed logos

Includes

- Inflation System: Master Blaster Electric Inflator and hose kit.
- Stake Down Kit
- Repair Kit
- Instruction Manual

Fabric Colors

- White, orange, sand, green
- Other colors on request

Load Resistance

- Wind: 65mph
- Snow: 3.1 lb/sqft

TAG Inflatable Shelter

The Number One Shelter for Emergency Situations, Rapid Deployment

| | | TAG 3A | TAG 4A | TAG 5A | TAG 6A |
|----------------------------------|-----------------------------------|----------------|----------------|----------------|----------------|
| Floor Space (sqft) | | 312 | 452 | 603 | 840 |
| External Dimensions | Length (ft) | 16'11" | 24'9" | 32'8" | 40'6" |
| | Width (ft) | 18'4" | 18'4" | 18'4" | 20'8" |
| | Height (ft) | 9'2" | 9'2" | 9'2" | 10'2" |
| Number of Arches | | 3 | 4 | 5 | 6 |
| Packing Information LxWxH | Tent | 47x39x26/337lb | 51x39x28/419lb | 55x39x30/507lb | 59x39x35/456lb |
| | Poles | 16x16x43/20lb | 16x16x43/31lb | 16x16x43/42lb | 16x16x43/53lb |
| Dimensions (inch) Weight (lb) | Pegs & Hammer | 16x16x24/45lb | 16x16x24/57lb | 16x16x24/62lb | 16x16x24/66lb |
| | Electrical Inflator Repair Kit | 24x24x43/29lb | 24x24x43/29lb | 24x24x43/29lb | 24x24x43/29lb |
| Total Weight (lb) | | 431 | 536 | 640 | 604 |
| Setup Time (Min) | | 4 | 5 | 6 | 6 |
| # Tents/20' Container | | 15 | 15 | 12 | 12 |

